



moffatt & nichol

Chile Earthquake and Tsunami of February 27th, 2010

ASCE/COPRI RECONNAISSANCE

Presented by:

Omar Jaradat, Ph.D., P.E.,

Marc Percher, P.E.,

Arul Arulmoli, G.E., F.ASCE






Quake

- ◆ February 27, 2010
- ◆ 8.8 Magnitude
- ◆ 120+ seconds shaking
- ◆ Plate uplift
- ◆ Tsunami
 - ◆ 35ft run-up typical in south
 - ◆ 100ft run-up in Tirua
 - ◆ Decks overtopped 1ft in north
- ◆ Aftershocks up to 6.9 M





moffatt & nichol





Chile Earthquake Fault Rupture



Chile Earthquake (February 27, 2010)



moffatt & nichol

- ◆ More than 500 people lost lives
- ◆ Destroyed more than 500,000 homes
- ◆ Displaced over 1,000,000 people
- ◆ Estimated damage is more than \$20-\$30 Billion (US), equivalent to 10-15% of Chile's GDP





Earthquake Reconnaissance

◆ Chile

- ◆ April 10 to 17, 2010
- ◆ Organized by ASCE Coasts Oceans Ports and Rivers Institute (COPRI)
- ◆ 8 Marine & Coastal Engineering Professionals
 - ◆ Structural (Wharves, MOTs, Bridges)
 - ◆ Coastal (Tsunami, Coasts)
 - ◆ Geotechnical (Marine Structures)






Objectives

- ◆ Assess and learn from the performance of port infrastructure including:
 - ◆ Waterfront structures and Foundation systems
 - ◆ Handling equipments and Utilities
- ◆ Assess and learn from the effects of the earthquake and subsequent tsunami
- ◆ Identify infrastructure that performed as intended and the ones that performed poorly



moffatt & nichol



Site Investigations

1. Talcahuano
2. San Vicente Port
3. San Vicente Gas Terminal
4. Dichato
5. Port of Lirquen
6. Port of Coronel
7. Isla Santa Maria
8. Punta Tumbes
9. Valparaiso Port
10. San Antonio Port



moffatt & nichol






Observations

- ◆ Damage related to Tsunami
- ◆ Damage due to earthquake shaking – Inertia and kinematic loading
- ◆ Damage due to lateral spreading, slope failure, liquefaction, land vertical movement
- ◆ Indirect damage due to power failure, vessels, cranes, etc....




moffatt & nichol




moffatt & nichol

Observations Soil Slope Failures

Observations: Loss of Dikes/ Sheetpiles/ Retaining Walls



San Vicente



Talcahuano




Coronel



Talcahuano

- ◆ Loss of dike/sheetpile/retaining wall results in loss of backlands
- ◆ Tsunami removes evidence (if any) of liquefaction



Observations Soil Slope Failures

- ◆ Dry Season – It could have been worse!



moffatt & nichol



moffatt & nichol

Observations Concrete Pier / Wharf



San Vicente Port





moffatt & nichol






moffatt & nichol

Observations Steel Pier / Wharf



Port of Coronel








San Vicente Gas Terminal




MUELLE LO ROJAS - CORONEL



MUELLE LOTA BAJO






moffatt & nichol

Observations Kinematic Loading



Port of Coronel





moffatt & nichol

Observations Cranes and Base Isolated Pier



Port Lirquen



moffatt & nichol



Valparaiso Port




moffatt & nichol



Prevention First
2010

Based Isolated



ASCE COPR

Earth Mechanics Inc.
Geotechnical and Earthquake Engineering

Halcrow



Designed and constructed (including isolators) in Chile
No damage seen or measured (not instrumented)



Crane at base isolated structure hit by vessel

moftatt & nichol



Possibly due to interaction during earthquake



Observations Piping


- ◆ Performed well, no ruptured piping found, even where pounding or anchorage loss



moffatt & nichol



Coronel



Coronel





Observations Tanks

Courtesy of Bill Bruin,
Bay of San Vicente




◆ Outside scope of trip, can't help but look



Observations Tsunami – Impact Damage

- ◆ Much of the damage is from debris impact

Ialcandano





Observations Tsunami – Vessel Theft


- ◆ Breaks lines, carries away vessel





Observations Tsunami – Vessel Escape

- ◆ San Antonio – 7 of 9 berths filled at earthquake
- ◆ 1.5 hours later all vessels had escaped





Observations

Cranes – Vessel Escape

- ◆ During earthquake power lost
- ◆ Cranes left inside vessels or w/ hanging containers
- ◆ Vessel escapes – catches container / crane and damages it



San Antonio






Observations

Bollards – Vessel Escape

- ◆ Do not use quick release hooks in Chile (costs)
- ◆ Most bollards performed well, but San Antonio lost 3



moffatt & nichol





Lessons Learned

- ◆ Port Structures built to current **Building** code performed well
- ◆ Loss Retaining Walls → Loss Backlands
- ◆ Soil Movement impacts:
 - ◆ Structural Performance
 - ◆ Post-EQ Operability
- ◆ Cranes lose power → damaged by escaping vessel
- ◆ Operations **MUST** work around damage
- ◆ Debris impact causes majority of tsunami damage
 - ◆ **Rapid evacuation of vessels** reduces port damage significantly



Tsunami Recommendations

- ◆ Have
 - ◆ **EXISTING** vessel evacuation plan
 - ◆ Risk assessments to determine tsunami zone
 - ◆ Audible warning systems and signage
 - ◆ Plans for **VERTICAL** evacuation
- ◆ Design foundations for scour in tsunami zone
- ◆ Low lying buildings need flowthrough, anchorage, and low importance
- ◆ **Keep critical equipment away from lowlands**



moffatt & nichol



moffatt & nichol

Earthquake Recommendations

- ◆ Chile **NATIONAL** instrumentation program
- ◆ Consider soil movement in structural design
- ◆ Use anchored retaining structures, consolidated ground, in-depth geotechnical studies
- ◆ Quick release hooks at moorings **OR** balanced design for bollards
- ◆ Keep in mind post event resource limitations
 - ◆ Need steel plates, aggregate fill, etc.
 - ◆ Need engineers, inspectors, and regulators on board and best prepared



Questions?



moffatt & nichol